

# Kitchen/Garage Fire Extinguisher

Part number 466140

Regular use

Disposable

## UL Rated 5-B:C



## Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Kitchen/Garage unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.


## At a Glance

- Model KG
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

## Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



UPC: 0-47871-66140-4

## Product Specification

Net agent weight (Average)	2 lb
Unit weight (Average)	2.85 lb
Diameter	3.25 inches
Height	10.95 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

## Packaging Options



MASTER PACK