



*USI ELECTRIC, INC. brings 37 years of manufacturing expertise to a full line of safety products designed for the electrical industry.*



**Model USI-2430**

**Smoke & Fire Alarm (120 Volt AC Powered)**

**120 Volt AC Powered Heat Alarm with Battery Backup**

- 130°F (57°C) Fixed Temperature Alarm
- 9V Battery Backup in Event of AC Power Failure
- Includes 9 Volt Battery
- Interconnectable up to 18 units (12 units must be smoke alarms). When unit goes into alarm, all interconnected units sound their alarm.
- Originating Alarm Feature - when heat is detected, the red LED flashes on the initiating heat alarm
- Green LED indicator for AC power
- Separate large size 5<sup>5/8</sup>" (143mm) Mounting Ring Attaches to any Standard Rectangular or Octagon Junction Box and Covers Drywall Cutout - for easy installation and coverage of drywall cutouts.
- Fast and Easy Installation
- Test Button
- 120 VAC (60 Hz) Power
- Wire Harness for Easy Connection
- Mounts on Single, Gang or 4" (102mm) Octagon Junction Box
- Loud 85 Decibel Horn
- Five Year Limited Warranty



All USI ELECTRIC Smoke & Fire Alarms comply with the following authorities: Underwriters Laboratories (UL), Underwriters Laboratories Canada (ULC), Federal Housing Authority (FHA), Housing and Urban Development (HUD), National Fire Protection Association (NFPA), California State Fire Marshal (CSFM)

USI-2430						
	Size		Weight		Cube	UPC #
	English (inches)	metric (mm)	lbs.	kg.		
Giftbox	5 <sup>1/2</sup> " x 5 <sup>1/2</sup> " x 1 <sup>3/4</sup> "	139 x 139 x 44	.60	0.3	-----	0-42741-02430-3
Master Carton (24 pcs)	12" x 12" x 12"	317 x 317 x 317	14	6.0	1.05 Ft. <sup>3</sup>	1-00-42741-02430-0

**USI ELECTRIC, INC.**  
 7-A GWYNNS MILL COURT  
 OWINGS MILLS, MARYLAND 21117 USA  
 TELEPHONE: 800-390-4321 • FAX: 410-363-2218 • E-MAIL: sales@usielectric.com

Visit Us on the Web! [www.usielectric.com](http://www.usielectric.com)