

CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHERS



- **Carbon Dioxide**, a gaseous agent for class B and C fires.
- **Ideal Uses:** chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, airport ramps, boat docks and large laboratories.
- Manufactured to ANSI/UL 154 and ANSI/UL 711 standards.

SPECIFICATIONS	PORTABLE UNITS			
SIZE/MODEL	5CD	10CD	15CD	20CD
PART NO.	45100	45600	46100	46600
VALVE	CHROME PLATED BRASS			
CAPACITY lbs./kg)	5 • 2.27	10 • 4.54	15 • 6.80	20 • 9.07
U.L. Rating	5B:C	10B:C	10B:C	10B:C
Cylinder	ALUMINUM			
Ship wt. (lbs./kg)	13 ³ / ₄ • 6.3	27 ³ / ₄ • 12.6	37 ³ / ₄ • 17.1	49 • 22.2
Height (in./cm)	17 ³ / ₈ • 44.1	19 ³ / ₄ • 50.2	26 ³ / ₈ • 67.0	26 ⁷ / ₈ • 68.2
Width (in./cm)	8 ¹ / ₄ • 21.0	12 • 30.5	12 • 30.5	13 • 33.0
Diameter (in./cm)	5 ¹ / ₄ • 13.3	6 ¹⁵ / ₁₆ • 17.6	6 ⁷ / ₈ • 17.5	8 • 20.3
Bracket	Wall	Wall	Wall	Wall
Range (feet/meters)	4-8/1.2-2.4	4-8/1.2-2.4	4-8/1.2-2.4	4-8/1.2-2.4
Discharge time (seconds)	8	10	15	20
USCG Approved	Type B:C Size I		Type B:C Size II	

PRODUCT DATASHEET LINKS (PDF)

Part No.	45100	45600	46100	46600
----------	-----------------------	-----------------------	-----------------------	-----------------------