




- **Halotron™**, a HydroChloroFluoro Carbon nonconductive agent pressurized with Argon. Approved by the EPA and FAA as HCFC blend B for use on class "A", "B" and "C" type fires.
- This is an excellent replacement for Halon 1211.
- **IDEAL USES:** Computers, telephone switch gears, sensitive data storage areas, offices, boats, forest machines, aircraft flight lines, and mobile units.
- Manufactured to ANSI/UL 2129 and ANSI/UL 711 standards.

SPECIFICATIONS	OPERATING PRESSURE – 100PSI/690 kPa										125 PSI/862.5 kPa
	2.5F	2.5F V/B	2.5H	2.5H V/B	5F	5F V/B	5H	5H V/B	11	15	
Part No. Alum. Valve	70258	70251	70259	70256	70510	70550	75550	75555	71100	71550	
Part No. Brass Valve	-	-	-	-	70511	70551	75551	75556	71101	71551	
Capacity (lbs./kg)	2½ • 1.13	2½ • 1.13	2½ • 1.13	2½ • 1.13	5 • 2.27	5 • 2.27	5½ • 2.49	5½ • 2.49	11 • 4.99	15½ • 7.03	
U.L. Rating	2B:C	2B:C	2B:C	2B:C	5B:C	5B:C	5B:C	5B:C	1A:10B:C	2A:10B:C	
Ship Wt. Alum. Valve (lbs./kg)	5¼ • 2.38	5½ • 2.49	5½ • 2.49	5¾ • 2.61	9¼ • 4.2	9½ • 4.3	10 • 4.5	10¼ • 4.7	21¼ • 9.6	25¾ • 11.7	
Ship Wt. Brass Valve (lbs./kg)	-	-	-	-	9¼ • 4.4	10 • 4.5	10½ • 4.8	10¼ • 4.9	21¼ • 9.9	26¼ • 11.9	
Height (in./cm)	13¾ • 34.0	13¾ • 34.0	13¾ • 34.0	13¾ • 34.0	16¾ • 41.6	16¾ • 41.6	16¾ • 41.6	16¾ • 41.6	17½ • 44.5	17½ • 44.5	
Width (in./cm)	5½ • 14.3	5½ • 14.3	6¾ • 17.1	6¾ • 17.1	6¾ • 16.7	7½ • 18.6	6¾ • 16.7	7½ • 18.6	8½ • 21.9	8½ • 21.9	
Diameter (in./cm)	3¾ • 8.6	3¾ • 8.6	3¾ • 8.6	3¾ • 8.6	4¼ • 10.8	4¼ • 10.8	4¼ • 10.84	4¼ • 10.8	7 • 17.8	7 • 17.8	
Bracket	Wall	V/B	Wall	V/B	Wall	V/B	Wall	V/B	Wall	Wall	
Range (feet/meter)	6-10 • 1.8-3	6-10 • 1.8-3	6-10 • 1.8-3	6-10 • 1.8-3	9-15 • 2.7-4.5	9-15 • 2.7-4.5	9-15 • 2.7-4.5	9-15 • 2.7-4.5	9-15 • 2.7-4.5	12-18 • 3.7-5.5	
Discharge Times (seconds)	9	9	9	9	9	9	9	9	9	13	
Cylinder	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	
USCG Approved	N/A	N/A	N/A	N/A	Type B:C Size I					Type B:C Size II	

**PRODUCT DATASHEET LINKS (PDF)**

<b>Part No. Alum. Valve</b>	<a href="#">70258</a>	<a href="#">70251</a>	<a href="#">70259</a>	<a href="#">70256</a>	<a href="#">70510</a>	<a href="#">70550</a>	<a href="#">75550</a>	<a href="#">75555</a>	<a href="#">71100</a>	<a href="#">71550</a>
<b>Part No. Brass Valve</b>	--	--	--	--	<a href="#">70511</a>	<a href="#">70551</a>	<a href="#">75551</a>	<a href="#">75556</a>	<a href="#">71101</a>	<a href="#">71551</a>